

IN THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1-25 (canceled)

26. (currently amended) A device according to ~~claim 25~~ claim 35, wherein the evaluation unit (20) is adapted to determine a rotation angle of the polarization between the at least one electromagnetic wave (18), reflected by the object (16) and received by the receiver (14) and an electromagnetic wave emitted by the signal source.
27. (currently amended) A device according to ~~claim 25~~ claim 35, wherein the evaluation unit (20) is adapted to determine a type of polarization of the at least one electromagnetic wave (18) reflected by the object (16) and received by the receiver (14).
28. (currently amended) A device according to ~~claim 25~~ claim 35, wherein the evaluation unit (20) is adapted to determine a wavelength of the at least one electromagnetic wave (18) reflected by the object (16) and received by the receiver (14).
29. (currently amended) A device according to ~~claim 25~~ claim 35, wherein the signal source (10) is adapted to change at least one of an angle of polarization, a level of polarization and a type of polarization of the generated at least one electromagnetic wave (12), in order to generate at least two differently polarized electromagnetic waves (12).

30. (currently amended) A device according to ~~claim 25~~ claim 35, wherein the signal source (10) is adapted to change the wavelength of the generated at least one electromagnetic wave (12), in particular to generate at least two electromagnetic waves (12) with different wavelengths.
31. (previously presented) A device according to claim 30, wherein the evaluation unit (20) is adapted to determine on a basis of the evaluated polarization, to evaluate the properties of polarization of at least two electromagnetic waves with different wavelengths, to evaluate the ratio of the two electromagnetic waves.
32. (previously presented) A device according to claim 31, wherein the device is provided in a safety system of vehicle, and the evaluation unit (20) is adapted to generate as an evaluation signal (22) an information signal for controlling a passenger protection system (24, 26, 28, 30) on a basis of information on a determined surface of the object.
33. (previously presented) A device according to claim 32, wherein a control unit (24) of the passenger protection system includes a comparison unit (25), which compares the evaluation signal (22) with a threshold value (27), the control unit (24) being adapted to trigger at least one safety device (26, 28, 30) when the evaluation signal (22) exceeds the threshold value (27).
34. (previously presented) A device according to claim 33, wherein the control unit (24) of the passenger protection system is adapted to change the threshold value (27) dependent on the evaluation signal (22).

35. (currently amended) ~~A device according to claim 25~~ A device for object recognition, the device comprising:
- a signal source (10), adapted to generate at least one electromagnetic wave (12) which may be reflected by an object;
- a receiver (14) for receiving the at least one electromagnetic wave (18) reflected by the object (16); and
- an evaluation unit that evaluates a polarization of the at least one electromagnetic wave (18) reflected by the object (16) and received by the receiver (14) and generates at least one evaluation signal (22), wherein the device is used in a pre-crash-system, a cV-system, an ADC-system a warning system for obstacle and/or slippery ice and/or a recognition system for roadway conditions.
36. (currently amended) ~~A device according to claim 25~~ claim 35, wherein the receiver (14) is adapted to change its receiving characteristics controlled by the evaluation unit (20).
37. (currently amended) ~~A device according to claim 25~~ claim 35, wherein the signal source (10) is adapted to generate at least one linear, circular or elliptically polarized electromagnetic wave, having a wavelength in the region of visible light.
38. (canceled)
39. (currently amended) ~~A method according to claim 38~~ claim 45, wherein a rotation angle of the polarization between the at least one electromagnetic wave (18), reflected by the object (16) and received and emitted, is determined.

40. (currently amended)A method according to ~~claim 38~~ claim 45, wherein a type of polarization of the at least one electromagnetic wave (18), reflected by the obstacle (16) and received, is determined.
41. (currently amended)A method according to ~~claim 38~~ claim 45, wherein a wavelength of the at least one electromagnetic wave (18), reflected by the object (16) and received, is determined.
42. (currently amended)) A method according to ~~claim 38~~ claim 45, wherein at least one of an angle of polarization, a level of polarization and a type of polarization of the generated at least one electromagnetic wave (12) is changed, wherein two or more electromagnetic waves (12) having polarizations different from each other are emitted.
43. (currently amended)A method according to ~~claim 38~~ claim 45, wherein a wavelength of the generated at least one electromagnetic wave (12) is changed, wherein two or more electromagnetic waves (12) having wavelengths different from each other are emitted.
44. (canceled)
45. (currently amended)~~A method according to claim 44,~~ A method of object recognition comprising:
generating and emitting at least one electromagnetic wave, wherein the at least one electromagnetic wave is reflected by an object;
receiving the at least one electromagnetic wave reflected by the object;
evaluating a polarization of the received at least one electromagnetic wave;

generating an evaluation signal based on the evaluation of the received electromagnetic wave;

determining a surface structure of the object based on the evaluated polarization;
and wherein the method is used in a vehicle passenger protection system and on
the basis of information on the determined surface structure the passenger
protection system (24, 26, 28, 30) is controlled

controlling a passenger protection system (24, 26, 28, 30) based on the
determined surface structure.

46. (currently amended) A method according to ~~claim 38~~ claim 45, wherein at least one of emitting characteristics when emitting and receiving characteristics when receiving the at least one electromagnetic wave (18) reflected by the object (16) is changed.
47. (currently amended) A method according to ~~claim 38~~ claim 45, wherein at least one linear, circular or elliptically polarized electromagnetic wave, having a wavelength in the region of visible light, is generated.
48. (currently amended) A method according to ~~claim 38~~ claim 45, wherein a non-polarized electromagnetic wave is emitted and its reflection at the object is analyzed with regard to properties of polarization portions and directions contained in the reflected wave, and information thus obtained is compared with stored information on polarizations of reflected waves at certain materials.